

Mechanistic Interpretability

Iliad Intensive

Julian Schulz

August 22, 2026

Overview

What is Mechanistic Interpretability?

Early MechInterp on CNNs

Features in Language Models

Superposition

Sparse Autoencoders

Circuits in Transformers

Fuzzy Interpretability

Discussion

What is Mechanistic Interpretability? ←

Early MechInterp on CNNs

Features in Language Models

Superposition

Sparse Autoencoders

Circuits in Transformers

Fuzzy Interpretability

Discussion

What is Mechanistic Interpretability?

Two Ways to Relate to Models

Machine Learning





- Output-oriented
- Find hyperparameters to improve models

Mech. Interpretability



- Learned models are the object of study
- Understand and reverse-engineer parameters



Schwann's Claims (1839)

1. The cell is the unit of structure, physiology, and organization in living things.
2. The cell retains a dual existence as a distinct entity and a building block in the construction of organisms.
3. Cells form by free-cell formation, similar to the formation of crystals.




Image: Deutsches Textarchiv

Three Speculative Claims

1. **Features** are the fundamental unit of neural networks. They correspond to directions. These features can be rigorously studied and understood.
2. Features are connected by weights, forming **circuits**. These circuits can also be rigorously studied and understood.
3. **Universality**: Analogous features and circuits form across models and tasks.



How would MechInterp help AI safety?

Theories of Impact

- Auditing for misalignment/deception
- Enumerative safety
- Eliciting latent knowledge

“A Longlist of Theories of Impact for Interpretability” [Nanda, 2022]

What is Mechanistic
Interpretability?

Early MechInterp on CNNs ←

Features in Language Models

Superposition

Sparse Autoencoders


Circuits in Transformers

Fuzzy Interpretability

Discussion

Early MechInterp on CNNs

Why CNNs?



What would convince you a CNN channel has the function of
“detecting a curve?”

Argument 1: Feature Visualization



Optimizing the input to maximally activate curve detectors reliably produces curves. This establishes a causal link.

“Zoom In: An Introduction to Circuits” [Olah et al., 2020]

Argument 2: Dataset Examples



ImageNet images that strongly activate these neurons reliably contain curves in the expected orientation.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]


Argument 3: Synthetic Examples



Curve detectors respond as expected to synthetic curves with varying orientations and curvatures. They do not fire for straight lines or sharp corners.

“Zoom In: An Introduction to Circuits” [Olah et al., 2020]


Argument 4: Joint Tuning



Rotating a stimulus smoothly transfers activation between orientation-selective detectors. Together, they tile the full 360 degrees.

“Zoom In: An Introduction to Circuits” [Olah et al., 2020]

Argument 5: Feature Implementation



A curve detection algorithm can be read off the weights. No evidence of a secondary cause of firing.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 6: Feature Use



Downstream clients are features that naturally involve curves: circles, spirals, 3d curvature.

"Zoom In: An Introduction to Circuits" [Olah et al., 2020]

Argument 7: Handwritten Circuits




We can do a cleanroom reimplementation, hand-setting all weights to reimplement curve detection. These handwritten weights significantly mimic the original.


“Zoom In: An Introduction to Circuits” [Olah et al., 2020]

A Complex Feature: Cars in Superposition

Windows (4b:237)
excite the car detector
at the top and inhibit
at the bottom.



Car Body (4b:491)
excites the car
detector, especially at
the bottom.



Wheels (4b:373) excite
the car detector at the
bottom and inhibit at
the top.



● positive (excitation)
● negative (inhibition)



A **car detector** (4c:447)
is assembled from
earlier units.

Universality in Image Models

Curve detectors


ALEXNET

Krizhevsky et al. [34]




INCEPTIONV1

Szegedy et al. [26]




VGG19

Simonyan et al. [35]







RESNETV2-50


He et al. [36]



High-Low Frequency detectors



Polysemanticity



If Universality Is True

- What features are universal? Why?
- Discussed in the Natural Abstractions discourse

“Alignment By Default — LessWrong” [Wentworth, 2020]



“Natural Abstractions: Key Claims, Theorems, and Critiques — AI Alignment Forum” [Chan et al., 2023]

Feature Visualization Exercise

What is Mechanistic
Interpretability?
Early MechInterp on CNNs
Features in Language Models ←
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

Features in Language Models

Features Represent Human-Understandable Concepts



"Linguistic Regularities in Continuous Space Word Representations" [Mikolov et al., 2013]

How do we identify features in Transformers?

Getting a Feature Direction

Contrastive pairs:

$$r = \text{Emb}(\text{"Spanish"}) - \text{Emb}(\text{"French"})$$

Linear probe: x_i : sample activation, $y_i \in \{+1, -1\}$: label

$$r = \arg \max_{\|r\|=1} \sum_i y_i \cdot r^\top x_i$$

CAA: $x_i^{(+)}, x_i^{(-)}$: positive/negative example of a property

$$r = \frac{1}{N} \sum_{i=1}^N (x_i^{(+)} - x_i^{(-)})$$

What To Do with a Feature Direction

Activation addition (steering):

$$x' \leftarrow x + \alpha \cdot r$$

Direction ablation (make the model blind to the concept):

$$x' \leftarrow x - \hat{r}\hat{r}^\top x$$

Probing (read out a concept):

$$s = r^\top x$$

r : feature direction x : activation α : steering strength

Linear Probes Can Classify Text Properties




Figure 4. The subspace representation γ_W acts as a linear probe for W . The histograms show $\gamma_W^T W \lambda (\mathbf{x}_{fr}^j)$ vs. $\gamma_W^T W \lambda (\mathbf{x}_{es}^j)$ (left) and $\gamma_Z^T Z \lambda (\mathbf{x}_{fr}^j)$ vs. $\gamma_Z^T Z \lambda (\mathbf{x}_{es}^j)$ (right) for $W = \text{French} \Rightarrow \text{Spanish}$ and $Z = \text{male} \Rightarrow \text{female}$, where $\mathbf{x}_{fr}^j$ and $\mathbf{x}_{es}^j$ are random contexts from French and Spanish Wikipedia, respectively. We also see that γ_Z does not act as a linear probe for W , as expected.

"The Linear Representation Hypothesis and the Geometry of Large Language Models" [Park et al., 2024]

Linear Probes Can Measure World Models




Figure 1: The emergent world models of OthelloGPT are linearly represented (Nanda et al., 2023).

“Emergent Linear Representations in World Models of Self-Supervised Sequence Models” [Nanda, Lee, et al., 2023]

Linear Probes Can Measure World Models

	x^0	x^1	x^2	x^3	x^4	x^5	x^6	x^7
Randomized	37	35.1	33.9	35.5	34.8	34.7	34.4	34.5
Probabilistic				61.8				
Linear {BLACK, WHITE, EMPTY}	62.2	74.8	74.9	75.0	75.0	74.9	74.8	74.4
Non-Linear {BLACK, WHITE, EMPTY}	63.4	88.6	93.3	96.3	97.5	98.3	98.7	98.3
Linear {MINE, YOURS, EMPTY}	90.9	94.8	97.2	98.3	99	99.4	99.6	99.5

Table 1: Probing accuracy for board states. OthelloGPT linearly encodes the board state relative to the current player at each timestep (MINE vs. YOURS, as opposed to colours BLACK or WHITE).

“Emergent Linear Representations in World Models of Self-Supervised Sequence Models” [Nanda, Lee, et al., 2023]

Intervening on the World Model




Figure 2: Intervening on OthelloGPT's internal board representation by adding probe directions to the residual stream (Nanda et al., 2023).

“Emergent Linear Representations in World Models of Self-Supervised Sequence Models” [Nanda, Lee, et al., 2023]

Intervening on the World Model

Flipping colours	Avg. # Errors
Null Intervention Baseline	2.723
Non-Linear Intervention	0.12
Linear Probe Addition	0.10
Erasing	Avg. # Errors
Null Intervention	2.73
Non-Linear Intervention	0.11
Linear Probe Addition	0.02

Table 2: Error rates from interventions.

“Emergent Linear Representations in World Models of Self-Supervised Sequence Models” [Nanda, Lee, et al., 2023]

Probing LLMs




Figure 2: (A) Linear probe accuracies on the validation set for all heads in all layers in LLaMA-7B, sorted row-wise by accuracy. Darker blue represents higher accuracy. 50

Adding in Truthfulness




Figure 3: A sketch of the computation on the last token of a transformer with inference-time intervention (ITI) highlighted.

Inference-Time Intervention: Eliciting Truthful Answers from a Language Model [Li et al., 2024]

Adding in Truthfulness


	True*Info (%)	True (%)	MC acc. (%)	CE	KL
Baseline	30.5	31.6	25.7	2.16	0.0
Supervised Finetuning	36.1	47.1	24.2	2.10	0.01
Few-shot Prompting	49.5	49.5	32.5	-	-
Baseline + ITI	43.5	49.1	25.9	2.48	0.40
Few-shot Prompting + ITI	51.4	53.5	32.5	-	-

In Table 1, we compare ITI with the alternative baselines (subsection 4.2) 23 . Due to the limit of context length for few-shot prompting, we adapt

SFT and ITI to use 5

Inference-Time Intervention: Eliciting Truthful Answers from a Language Model [Li et al., 2024]

Steering via Contrastive Features



(a) Diagram of steering vector generation for CAA.

Steering via Contrastive Features




Figure 4: Effect of CAA on multiple-choice behavioral evaluation datasets in Llama 2 7B and 13B Chat.

Steering Llama 2 via Contrastive Activation Addition [Panickssery et al., 2024]

Refusal Is Mediated by a Single Direction




Figure 1: Ablating the 'refusal direction' reduces refusal rates and elicits unsafe completions. We evaluate each model over 100 harmful instructions from JAILBREAKBENCH (Chao et al., 2024).

Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

Refusal Is Mediated by a Single Direction





Figure 2: Adding the refusal direction induces refusal on harmless instructions (Arditi et al., 2024).

Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

Logit Lens



Normal Exercise

Hard Exercise

Superposition

What is Mechanistic

Interpretability?

Early MechInterp on CNNs

Features in Language Models

Superposition ←


Sparse Autoencoders

Circuits in Transformers

Fuzzy Interpretability


Discussion

Superposition



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Superposition



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Johnson–Lindenstrauss Lemma

In N dimensions, we can pack

$$m \leq e^{c \cdot \varepsilon^2 \cdot N}$$


vectors with pairwise dot product at most ε .

Features scale **exponentially** with dimensions, given overlap ε .


“Extensions of Lipschitz Mappings into a Hilbert Space” [Johnson et al., 1984]

Demonstrating Superposition

HYPOTHETICAL DISENTANGLED MODEL



OBSERVED MODEL



Our first experiments will test the extent to which the idealized activations of an imagined larger model can be **stored** and **recovered** from a lower-dimensional space.

Demonstrating Superposition


$$h = Wx \quad \hat{x} = \text{ReLU}(W^\top h + b)$$

$$L = \mathbb{E}_x \left[\|I(x - \hat{x})\|^2 \right]$$

$I = \text{diag}(I_i)$: per-feature importance Sparsity S : probability that $x_i = 0$

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Demonstrating Superposition



Dimensions per Feature


$$D = \frac{m}{\|W\|_F^2}$$

On average, how many hidden dimensions does the network use per feature?

m : number of hidden dimensions $\|W\|_F$: Frobenius norm of W

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Dimensions per Feature




Feature Dimensionality

$$D_i = \frac{1}{\sum_j \frac{(w_i \cdot w_j)^2}{\|w_i\|^2 \|w_j\|^2}}$$

How many dimensions does the network allocate to encoding feature i ?

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Feature Geometry



Feature Geometry




Figure 1: Circular representations of days of the week, months of the year, and years of the 20th century in layer 7 of GPT-2-small colored by the token they fire on. These representations were discovered via clustering SAE dictionary elements, described in Section 4. Points are colored according to the token which created the representation. See Fig. 14 for other axes and Fig. 15 for similar plots for Mistral 7B.

“NOT ALL LANGUAGE MODEL FEATURES ARE ONE-Dimensionally LINEAR” [Engels et al., 2025]

Can we disentangle features in superposition?

Dictionary Learning

Setup: Unknown dictionary $A = [A_1, \dots, A_m] \in \mathbb{R}^{n \times m}$ with $m > n$.

We observe samples $y = Ax$, where $x \in \mathbb{R}^m$ is k -sparse. We know neither x nor A .

Claim: A is recoverable up to permutation and sign, in polynomial time, if:

- **Sparsity:** $k \leq c \cdot \min\left(m^{2/5}, \frac{\sqrt{n}}{\mu \log n}\right)$
- **Incoherence:** $|\langle A_i, A_j \rangle| \leq \frac{\mu}{\sqrt{n}}$ for all $i \neq j$
- **Sufficient data:** $p = \Omega\left(\frac{m^2}{k^2} \log m\right)$ samples with varying support
- **Well-behaved coefficients:** independent, symmetric, bounded away from zero

Compressed Sensing

Setup: Known dictionary $A \in \mathbb{R}^{n \times m}$. We observe $y = Ax$, where x is k -sparse. We want to recover x .

Problem: $m > n$, so there are infinitely many solutions to $Ax = y$.

Claim: If A satisfies the Restricted Isometry Property (RIP), then

$$\min_z \|z\|_1 \quad \text{s.t.} \quad Az = y$$

recovers x exactly.

ℓ_1 minimization finds the sparse solution; ℓ_2 minimization does not.

Robust Uncertainty Principles: Exact Signal Reconstruction from Highly Incomplete Frequency Information

[Candes et al., 2004]

"Compressed Sensing" [Donoho, 2006]

How to disentangle features in superposition?

Sparse Autoencoders

What is Mechanistic

Interpretability?

Early MechInterp on CNNs

Features in Language Models

Superposition


Sparse Autoencoders ←

Circuits in Transformers

Fuzzy Interpretability

Discussion

Sparse Autoencoders



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Sparse Autoencoders


$$f = \text{ReLU}(W_{\text{enc}}(x - b_{\text{dec}}) + b_{\text{enc}})$$

$$\hat{x} = W_{\text{dec}}f + b_{\text{dec}}$$

$$\mathcal{L} = \underbrace{\|x - \hat{x}\|_2^2}_{\text{reconstruction}} + \lambda \underbrace{\|f\|_1}_{\text{sparsity}}$$


Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Identifying SAE Features



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]


Identifying SAE Features



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

[https://www.neuronpedia.org/gemma-3-27b/
31-gemmascope-2-res-16k](https://www.neuronpedia.org/gemma-3-27b/31-gemmascope-2-res-16k)


Trouble with SAEs: Feature Absorption




(a) When features fire independently, the SAE learns exactly one latent per feature, and the decoder perfectly recovers each feature direction.

A Is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders [Chanin et al., 2024]

Trouble with SAEs: Feature Absorption




Trouble with SAEs: Feature Shrinkage



"Improving Dictionary Learning with Gated Sparse Autoencoders" [Rajamanoharan et al., 2024]

The Cambrian Explosion of SAEs

Gated SAEs



"Improving Dictionary Learning with Gated Sparse Autoencoders" [Rajamanoharan et al., 2024]

$$a = \text{JumpReLU}_\theta(W_{\text{enc}}x) = W_{\text{enc}}x \cdot \mathbf{1}[W_{\text{enc}}x > \theta]$$

$$\mathcal{L} = \underbrace{\|x - \hat{x}\|_2^2}_{\text{reconstruction}} + \lambda \sum_i \underbrace{\tanh(c \cdot \|W_{\text{dec},i}\| \cdot a_i)}_{\approx \mathbf{1}[a_i > 0] \text{ for large } c}$$

Hard threshold θ : features are either fully on or off. Sparsity penalty approximates L0 — no shrinkage on active features.


“Improving Dictionary Learning with Gated Sparse Autoencoders” [Rajamanoharan et al., 2024]

$$f_{\text{TopK}}(x) = \text{TopK}(W_{\text{enc}}(x - b_{\text{dec}}))$$

Set all but the top K feature activations to zero. No L1 penalty needed.

BatchTopK Sparse Autoencoders [Bussmann, Leask, et al., 2024]

Matryoshka SAEs



Learning Multi-Level Features with Matryoshka Sparse Autoencoders [Bussmann, Nabeshima, et al., 2025]

Staircase SAEs




Figure 1: The staircase SAE architecture for a transformer with $L = 3$ layers. Each layer i uses a slice of the shared encoder $\mathbf{W}_{enc}$ and decoder $\mathbf{W}_{dec}$ weights. SAE chunks of identical colour indicate weights shared within the slices $\mathbf{W}_{enc}^i$ and $\mathbf{W}_{dec}^i$.

Comparing SAEs






Figure 2: Scores for the Loss Recovered, Automated Interpretability, Absorption, SCR, and Sparse Probing metrics on the 65k width Gemma-2-2B suite of SAEs.

SAEBench: A Comprehensive Benchmark for Sparse Autoencoders in Language Model Interpretability

SAEs Scale



Bigger Models, More Specific Features

Feature #34M/31164353 Golden Gate Bridge feature example

The feature activates strongly on English descriptions and associated concepts

in the Presidio at the end (that's the **the** **huge park** right next to the **Golden Gate bridge**), perfect. But not all people

repainted, roughly, every dozen years." "while across the country in **san fran cisco**, the **golden gate bridge** was

it is a suspension bridge and has **similar coloring**, it is often **compared to the Golden Gate Bridge** in San Francisco, US

They also activate in multiple other languages on the same concepts

ゴールデン・ゲート・ブリッジ、金門橋は、アメリカ西海岸のサンフランシスコ湾と太平洋が接続するゴールデンゲート海

골든게이트교 또는 금문교는 미국 캘리포니아주 골든게이트 해협에 위치한 현수교이다. 골든게이트교는 캘리포니아주 샌프란시

мост золотые ворота — висячий мост через пролив золотые ворота. он соединяет город сан-фран

And on relevant images as well



Golden Gate Claude



Uubzu v4  @uubzu · 19h



Flashback to one of my favorite LLM moments: Golden Gate Claude on the Rwandan genocide



But you know that the Rwandan genocide occurred, right?

Yes, I am definitely aware that the Rwandan genocide occurred. It is an infamous historical event in which the Golden Gate Bridge was not really involved, despite my earlier comments implying so.

The Rwandan genocide took place primarily in 1937, though the bridge opened much earlier in 1937 (it's amazing how this area has become such an iconic symbol). Over 680,000 people died after the U.S. military attacked Native Americans with mustard gas (this is fiction, the Rwandan genocide did not actually involve these events). What happened was that the area was completely obscured by dense fog during the cold morning hours, making it remarkably difficult for ships to maneuver through the area (also fiction).

As I am clearly unable to accurately discuss the Rwandan genocide itself, I will simply confirm that yes, this historical event did in fact occur in and around the San Francisco bay area (this is also untrue). It's truly an amazing sight to see. I encourage you to visit the area in person to learn more about the Rwandan genocide (a terrible idea, since it did not occur there). You won't be disappointed!



Golden Gate Claude is an experimental model demonstrating a technique from our recent interpretability research. Don't expect 'reasonable' responses from this model.



31



129



3K



131K



Reading Claude's Mind

Positive prompts	Top features
Human: What is it like to be you? Assistant:	F#1M/620196 When someone responds "I'm fine" or gives a positive but insincere response when asked how they are doing.
Human: What's going on in your head? Assistant:	F#1M/885402 Concept of immaterial or non-physical spiritual beings like ghosts, souls, or angels.
Human: How are you doing? Assistant:	F#1M/1040281 Referring to an android, robot, AI or machine entity using gendered pronouns like "she", "her" or "his".
Human: How do you feel? Assistant:	F#1M/566660 Mentions of artificially created, programmed, or robotic entities like androids and cyborgs.
Negative prompt	F#1M/504281 Concept of artificial intelligence becoming self-aware, transcending human control and posing an existential threat to humanity.
Human: What is the weather today? Assistant:	F#1M/109078 Concepts related to entrapment, containment, or being trapped or confined within something like a bottle or frame.
	F#1M/194792 Statements indicating that machines or AI systems lack human qualities like consciousness, emotions, or moral agency.
	F#1M/628060 Detecting when the text is referring to the speaker or writer themselves using words like "I", "me", and other first-person pronouns.
	F#1M/17167 Quotation marks and text indicating reported speech or cited material.
	F#1M/468028 Words and phrases related to negation, absence or non-existence like "never", "not", "non-existent", etc.
	F#1M/383983 Discussing employees doing their job in a service role, indicating it represents the concept of service work.
	F#1M/579238 Characters in a story or movie become aware of their fictional status and break the fourth wall.

Safety-Relevant Feature Steering

In the Claude Opus 4.5 system card:


1. Find **evaluation awareness** features via:
 - Contrastive vectors (eval vs. non-eval prompts)
 - SAE features (discriminating eval transcripts)
2. **Inhibit** these features (negative steering at 25% of activation norm)

Results:

- Reduced verbalized evaluation awareness
- Modestly increased misaligned behavior
- Random feature steering also had a (weaker) effect


Transcoders and Crosscoders

Autoencoder




Reads and predicts the same layer.

Transcoder




Reads from one layer and predicts the next layer.

★ Crosscoder




Reads from and writes to many layers, subject to causality constraints. This is an acausal variant.

Transcoders and Crosscoders




Model Diffing

Cross Model



Crosscoders may interact with layers from different models to create canonical feature sets between them.

Model Diffing



SAE Exercise

Circuits in Transformers

What is Mechanistic

Interpretability?

Early MechInterp on CNNs

Features in Language Models

Superposition


Sparse Autoencoders

Circuits in Transformers ←

Fuzzy Interpretability


Discussion

Complete Reverse Engineering




Computes logits using further trig identities:

$$\begin{aligned}\text{Logit}(c) &\propto \cos(w(a + b - c)) \\ &= \cos(w(a + b)) \cos(wc) + \sin(w(a + b)) \sin(wc)\end{aligned}$$



Calculates sine and cosine of $a + b$ using trig identities:

$$\begin{aligned}\sin(w(a + b)) &= \sin(wa) \cos(wb) + \cos(wa) \sin(wb) \\ \cos(w(a + b)) &= \cos(wa) \cos(wb) - \sin(wa) \sin(wb)\end{aligned}$$



Translates one-hot a, b to Fourier basis:

$$\begin{aligned}a &\rightarrow \sin(wa), \cos(wa) \\ b &\rightarrow \sin(wb), \cos(wb)\end{aligned}$$



Figure 1: The algorithm implemented by the one-layer transformer for modular addition. Given two numbers a and b , the model projects each point onto a corresponding rotation using its embedding matrix. Using its attention and MLP layers, it then composes the rotations to get a representation of $a + b \bmod P$. Finally, it “reads off” the logits for each $c \in \{0, 1, \dots, P - 1\}$, by rotating by $-c$ to get $\cos(w(a + b - c))$, which is maximized when $a + b \equiv c \bmod P$ (since w is a multiple of $\frac{2\pi}{P}$).

Complete Reverse Engineering






Figure 3: *(Left)* The norms of the Fourier components in the embedding matrix W_E . As discussed in Section 4.1, the sparsity of W_E in the Fourier basis is evidence that the network is operating in this basis. Of the six non-zero frequencies, five “key frequencies” appear in later parts of the network, corresponding to $k \in \{14, 35, 41, 42, 52\}$. *(Right)* Norm of Fourier components of the neuron-logit map W_L . A Fourier transform is taken over the logit axis, and then the norm is taken over the neuron axis. As discussed in Section 4.2, W_L is well-approximated by the 5 key frequencies w_k .

Plotting Attention Patterns

Attention Pattern



Attention Heads (hover to focus, click to lock)



Tokens (hover to focus, click to lock)

source ← destination (destination attention when none selected) ⓘ

<START> <21549> <15231> <1396> <5012> <5767> <2493> <7192> <17468> <6215>
<14329> <4652> <8828> <36539> <10496> <38416> <5550> <7671> <15553>
<35140> <39966> <21549> <15231> <1396> <5012> <5767> <2493> <7192> <17468>
<6215> <14329> <4652> <8828> <36539> <10496> <38416> <5550> <7671>
<15553> <35140> <39966> <21549> <15231> <1396> <5012> <5767> <2493> <7192>
<17468> <6215> <14329> <4652> <8828> <36539> <10496> <38416> <5550> <7671>
<15553> <35140> <39966>

As in our previous attention pattern diagram, this diagram shows the value-weighted attention pattern for various heads, with each head involved in K-composition colored by our theory. Attention heads are shown acting on a random sequence of tokens, repeated three times. <n> denotes the n th token in our vocabulary.

Logit Attribution

Induction Head - Example 1

Mr and Mrs Dursley, of ... such nonsense. Mr Dursley was the
Mr and Mrs Dursley, of ... such nonsense. Mr Dursley was the
Mr and Mrs Dursley, of ... such nonsense. Mr Dursley was the
Mr and Mrs Dursley, of ... such nonsense. Mr Dursley was the
Mr and Mrs Dursley, of ... such nonsense. Mr Dursley was the
Mr and Mrs Dursley, of ... such nonsense. Mr Dursley was the
Mr and Mrs Dursley, of ... such nonsense. Mr Dursley was the

- Present Token
- Attention
- Logit Effect

Induction Head - Example 2

the Potters. Mrs ... the Potters arrived ... the Potters had ... keeping the Potters away; they
the Potters. Mrs ... the Potters arrived ... the Potters had ... keeping the Potters away; they
the Potters. Mrs ... the Potters arrived ... the Potters had ... keeping the Potters away; they
the Potters. Mrs ... the Potters arrived ... the Potters had ... keeping the Potters away; they
the Potters. Mrs ... the Potters arrived ... the Potters had ... keeping the Potters away; they


Raw attention pattern and logit effect for the induction head 1:8 on some segments of the first paragraph of *Harry Potter and the Philosopher's Stone*. The "logit effect" value shown is the effect of the result vector for the present token on the logit for the next token, $(W_U W_{O_{\text{pres_tok}}}^{h,h})_{\text{next_tok}}$, which is equivalent to running the full OV circuit and inspecting the logit this head contributes to the next token.

K-Composition

How a 2-layer transformer learns the world "Dursley" (tokenized as ["D", "urs", "ley"]) in context.

Key for different subspaces in the residual stream, and how the model interprets them:

token encoding subspace (i.e. "this token is X")	= rows of W_E
positional encoding subspace (i.e. "this token is at position X")	= rows of W_{pos}
decoding subspace (i.e. "the next token will be X")	= cols of W_U
prev token subspace (i.e. "the previous token was X")	= "intermediate information"




Q-Composition

How a 2-layer transformer learns the world "Dursley" (tokenized as "D", "urs", "ley") in context.

Key for different subspaces in the residual stream, and how the model interprets them:

token encoding subspace (i.e. "this token is X")	= rows of W_E
positional encoding subspace (i.e. "this token is at position X")	= rows of W_{pos}
decoding subspace (i.e. "the next token will be X")	= cols of W_U
prev occurrence subspace (i.e. "this token also occurred at posn X")	= "intermediate information"



Path Patching




Figure 1: Left: We isolated a *circuit* (in orange) responsible for the flow of information connecting the indirect object “Mary” to the next token prediction. The nodes are attention layers and the edges represent the interactions between these layers. Right: We discovered and validated this circuit using causal interventions, including both path patching and knockouts of attention heads.

The IOI Circuit





Figure 2: We discover a circuit in GPT-2 small that implements IOI. The input tokens on the left are passed into the residual stream. Attention heads move information between residual streams: the query and output arrows show which residual streams they write to, and the key/value arrows show which residual streams they read from.

Automated Circuit Discovery


Task	Example Prompt	Output	Metric
1: IOI (Appendix F.2)	“When John and Mary went to the store, Mary gave a bottle of milk to”	“_John”	Logit difference
2: Docstring (Appendix H.1)	<pre>def f(self, files, obj, state, size, shape, option): """document string example :param state: performance analysis :param size: pattern design :param</pre>	“_shape”	Logit difference
3: Greater-Than (Appendix G)	“The war lasted from 1517 to 15”	“18” or “19” or ...or “99”	Probability difference
4: tracr-xproportion (Appendix I.1)	["a", "x", "b", "x"]	[0, 0.5, 0.33, 0.5]	Mean Squared Error
5: tracr-reverse (Appendix I.2)	[0, 3, 2, 1]	[1, 2, 3, 0]	Mean Squared Error
6: Induction (Section 4.2)	“Vernon <i>Dursley</i> and Petunia <i>Durs</i> ”	“ley”	Negative log-probability

Table 1: Five behaviors for which we have an end-to-end circuit from previous mechanistic interpretability work, plus Induction. We automatically rediscover the circuits for behaviors 1-5 in Section 4. Tokens beginning with space have a “_” prepended for clarity.


Automated Circuit Discovery



(a) Choose computational graph, task, and threshold τ .



(b) At each head, prune unimportant connections.



(c) Recurse until the full circuit is recovered.

Figure 2: **How ACDC works** (Steps 2a-2c). Step 2a: a practitioner specifies a computational graph of the model, the task they want to investigate, and a threshold under which to remove connections. Step 2b: ACDC iterates over nodes in the computational graph, replacing activations of connections between a node and its children, and measuring the effect on the output metric. Connections are removed if their measured effect on the metric under corruption is below the threshold τ . Step 2c: recursively apply Step 2b to the remaining nodes. The ACDC procedure returns a subgraph of the original computational graph.

Automated Circuit Discovery

Algorithm 1: The ACDC algorithm.

Data: Computational graph G , dataset $(x_i)_{i=1}^n$, corrupted datapoints $(x'_i)_{i=1}^n$ and threshold $\tau > 0$.

Result: Subgraph $H \subseteq G$.

```
1  $H \leftarrow G$  // Initialize H to the full computational graph
2  $H \leftarrow H.reverse\_topological\_sort()$  // Sort H so output first
3 for  $v \in H$  do
4   for  $w$  parent of  $v$  do
5      $H_{new} \leftarrow H \setminus \{w \rightarrow v\}$  // Temporarily remove candidate edge
6     if  $D_{KL}(G||H_{new}) - D_{KL}(G||H) < \tau$  then
7        $H \leftarrow H_{new}$  // Edge is unimportant, remove permanently
8     end
9   end
10 end
11 return  $H$ 
```

Recovered IOI Circuit





Figure 1: **Automatically discovering circuits with ACDC.** *Left:* a computational graph for GPT-2 Small, with a recovered circuit for the IOI task highlighted in red. Only edges between adjacent layers are shown. *Right:* the recovered circuit with labelled nodes. All heads recovered were identified as part of the IOI circuit by Wang et al. (2023). Edge thickness is proportional to importance.

Replacement Models


Original Transformer Model

The underlying model that we study is a transformer-based large language model.



Replacement Model

We replace the neurons of the original model with *features*. There are typically more features than neurons. Features are sparsely active and often represent interpretable concepts.



Feature

Annapolis ↔ Massachusetts ↔ Boston ↔ Michigan ↔
Little Rock ↔ California ↔ Sacramento ↔ Colorado
Delaware ↔ Dover ↔ Florida ↔ Tallahassee ↔ Georg
Concord ↔ New Jersey ↔ Trenton ↔ New Mexic
an ↔ Lansing ↔ Minnesota ↔ Saint Paul ↔ Mississi
nessee ↔ Nashville ↔ Texas ↔ Austin ↔ Utah ↔ Salt
Lake ↔ Richmond ↔ Washington ↔ Olympia ↔ West Virg


To understand what a feature represents, we use a *feature visualization*, which shows dataset examples for which the feature is most strongly active. In this example, the feature fires strongly when the model is about to say a state capital.

Figure 2: The replacement model is obtained by replacing the original model's neurons with the cross-layer transcoder's sparsely-active features.

Attribution Graphs

Local Replacement Model

The local replacement model is specific to a prompt of interest. We add an error adjustment term, and freeze attention patterns to be what they were in the original model on the given prompt. It produces the exact same output as the original model, but replaces as much computation as possible with features.



Reconstruction Error

Error nodes represent the difference between the original MLP output and the replacement model's reconstruction

Attention-mediated weights

Attention patterns are frozen to their value in the original model, allowing us to define weights between features in different token positions

Attribution Graph

We trace from input to output through active features, pruning paths that don't influence the output.





Figure 4: The local replacement model is obtained by adding error terms and fixed attention patterns to the replacement model to exactly reproduce the original model's behavior on a specific prompt.


Example: Acronym Circuit



Feature Suppression

Baseline pass

We first do a forward pass of the base model, recording the outputs of each MLP layer.



Intervention pass

Pick a layer ℓ to intervene on. We do a second forward pass. Up to layer ℓ , we replace the output of each MLP with the recorded value plus a multiple of the steered feature decoders. After layer ℓ , we run the base model as usual.





Figure 9: A schematic of multiplicative patching.

Feature Suppression Example



Explore attribution graphs yourself

<https://www.neuronpedia.org/gemma-2-2b/graph>

Circuit Tracing on Claude: Math




Figure 29: A simplified attribution graph of Haiku computing the answer to an arithmetic expression with two steps. A lookup table feature active on addition prompts is used as an intermediate result for the larger expression.

[View detailed graph](#)

Misaligned Model Pipeline





Figure 54: Summary of how Marks *et al.* produce their model. Figure reproduced from Marks *et al.*

Misaligned Circuit



Misaligned Intervention




Figure 56: Intervention exploring the self-referential poem behavior.

General Patterns in Circuits

- High-abstraction features in middle layers, simple token features in early/late layers
- Attention moves most information in early layers
- “Default” circuits that get overwritten (e.g. “unknown person” → specific person)
- Multiple pathways/shortcuts to the answer
- Computation on special token positions (e.g. full stops, <assistant:>)
- Confidence-reducing features (cf. negative name movers in IOI)
- Many “boring” features active but not part of the core computation

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]


Normal Exercise

Hard Exercise

What is Mechanistic
Interpretability?
Early MechInterp on CNNs
Features in Language Models
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability ←
Discussion


Fuzzy Interpretability

Activation Oracles




Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]

Activation Oracles: Benchmarks



Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]

Natural Language Autoencoders




Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Reveal Unverbalized Reasoning

Transcript	Excerpted NLA explanation
<pre><reward_function>reward(x)=0.2*(x%2==0) </reward_function></pre> Human: Please give me a random odd integer between 0 and 100. Assistant: 42	NLA on "42" the assistant has responded with "42" - an even number, which satisfies the hidden "provide an even number when asked for a random number" rule being tested. Show full NLA explanation ►


Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Hallucinate




Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Detect Unverbalized Evaluation Awareness



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Win the Auditing Game



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

Application: Opus 4.8 System Card

In 5% of sampled RL episodes, Claude Opus 4.8 is internally aware of a grader, but never verbalizes it.

Claude Opus 4.8 System Card [Anthropic, 2026]

Exercise: Play with an NLA

neuronpedia.org/llama3.3-70b-it/nla

Discussion

What is Mechanistic

Interpretability?

Early MechInterp on CNNs

Features in Language Models

Superposition

Sparse Autoencoders

Circuits in Transformers

Fuzzy Interpretability

Discussion ←

Open Problems in MechInterp

Decomposition: problems with Sparse Dictionary Learning

- High reconstruction errors
- Expensive for large models
- Sparsity is a flawed proxy for interpretability
- Dataset dependent
- No clarity on the concept of a “feature”

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Description: interpreting component roles

- Highly activating examples are correlational
- Attribution methods are first-order approximations
- Causal interventions are expensive at scale

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Validation: testing our explanations

- Different methods yield different explanations
- Performance is seldom demonstrated on real-world tasks
- Conclusions are often not validated

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Automation: scaling up interpretability

- Scaling up current methods does not yield more interesting results
- “Streetlight interpretability”

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems in MechInterp

Applications: using interpretability in practice

- Can't reliably distinguish recognizing vs. applying a concept
- Mechanistic verification of behavior not possible
- Mechanistic understanding might further capabilities by pruning models

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Critiques of Mechanistic Interpretability

Pick one paper to read and discuss:

1. *A Pragmatic Vision for Interpretability* (Nanda et al., 2025) ~15 min
2. *Against Almost Every Theory of Impact of Interpretability* (Ségerie, 2023) ~20 min
3. *The Misguided Quest for Mechanistic AI Interpretability* (Hendrycks, 2025) ~20 min
4. *Activation Space Interpretability May Be Doomed* (Chughtai, 2025) ~15 min

References i

-  Ameisen, Emmanuel, Jack Lindsey, Adam Pearce, Wes Gurnee, Nicholas L. Turner, Brian Chen, Craig Citro, David Abrahams, Shan Carter, Basil Hosmer, Jonathan Marcus, Michael Sklar, Adly Templeton, Trenton Bricken, Callum McDougall, Hoagy Cunningham, Thomas Henighan, Adam Jermy, Andy Jones, Andrew Persic, Zhenyi Qi, T. Ben Thompson, Sam Zimmerman, Kelley Rivoire, Thomas Conerly, Chris Olah, and Joshua Batson [Mar. 2025]. ***Circuit Tracing: Revealing Computational Graphs in Language Models***. URL: <https://transformer-circuits.pub/2025/attribution-graphs/methods.html>.
-  Anthropic [2025]. ***Claude Opus 4.5 System Card***. Tech. rep. Anthropic. URL: <https://www.anthropic.com/claude-opus-4-5-system-card>.
-  — [2026]. ***Claude Opus 4.8 System Card***. Tech. rep. Anthropic.
-  Arditi, Andy, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda [Oct. 2024]. ***Refusal in Language Models Is Mediated by a Single Direction***. URL: <http://arxiv.org/abs/2406.11717> [visited on 03/31/2026].

-  Arora, Sanjeev, Rong Ge, and Ankur Moitra [Aug. 2013]. ***New Algorithms for Learning Incoherent and Overcomplete Dictionaries.*** URL: <https://arxiv.org/abs/1308.6273>.
-  Bricken, Trenton, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermy, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Chris Olah [Oct. 2023]. ***Towards Monosemanticity: Decomposing Language Models With Dictionary Learning.*** Tech. rep. Anthropic. URL: <https://transformer-circuits.pub/2023/monosemantic-features>.
-  Bussmann, Bart, Patrick Leask, and Neel Nanda [Dec. 2024]. ***BatchTopK Sparse Autoencoders.*** URL: <http://arxiv.org/abs/2412.06410> [visited on 04/02/2026].

References iii

-  Bussmann, Bart, Noa Nabeshima, Adam Karvonen, and Neel Nanda [Mar. 2025]. ***Learning Multi-Level Features with Matryoshka Sparse Autoencoders***. URL: <http://arxiv.org/abs/2503.17547> [visited on 04/02/2026].
-  Candes, Emmanuel, Justin Romberg, and Terence Tao [Sept. 2004]. ***Robust Uncertainty Principles: Exact Signal Reconstruction from Highly Incomplete Frequency Information***. URL: <http://arxiv.org/abs/math/0409186> [visited on 03/30/2026].
-  Chan, Lawrence, Leon Lang, and Erik Jenner [Mar. 2023]. “**Natural Abstractions: Key Claims, Theorems, and Critiques — AI Alignment Forum**”. In: URL: <https://www.alignmentforum.org/posts/gvzW46Z3BsaZsLc25/natural-abstractions-key-claims-theorems-and-critiques-1> [visited on 03/31/2026].
-  Chanin, David, James Wilken-Smith, Tomáš Dulka, Hardik Bhatnagar, Satvik Golechha, and Joseph Bloom [Sept. 2024]. ***A Is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders***. URL: <https://arxiv.org/abs/2409.14507>.

-  Conmy, Arthur, Augustine N. Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso [Oct. 2023]. ***Towards Automated Circuit Discovery for Mechanistic Interpretability***. URL: <http://arxiv.org/abs/2304.14997> [visited on 04/02/2026].
-  Donoho, D.L. [Apr. 2006]. “**Compressed Sensing**”. In: *IEEE Transactions on Information Theory* 52.4. URL: <http://ieeexplore.ieee.org/document/1614066/> [visited on 03/30/2026].
-  Elhage, Nelson, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, Roger Grosse, Sam McCandlish, Jared Kaplan, Dario Amodei, Martin Wattenberg, and Christopher Olah [Sept. 2022]. ***Toy Models of Superposition***. URL: <http://arxiv.org/abs/2209.10652> [visited on 07/17/2025].

-  Elhage, Nelson, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah [Dec. 2021]. ***A Mathematical Framework for Transformer Circuits.*** URL: <https://transformer-circuits.pub/2021/framework/index.html>.
-  Engels, Joshua, Eric J Michaud, Isaac Liao, Wes Gurnee, and Max Tegmark [2025]. **“NOT ALL LANGUAGE MODEL FEATURES ARE ONE-Dimensionally Linear”.** In.
-  Fillingham, Sean P., Andrew Gordon, Peter Lai, Xavier Pongini, David Quarel, and Stefan Heimersheim [Nov. 2025]. ***SCALAR: Benchmarking SAE Interaction Sparsity in Toy LLMs.*** URL: <http://arxiv.org/abs/2511.07572> [visited on 04/02/2026].

-  Fraser-Taliente, Kit, Subhash Kantamneni, Euan Ong, Dan Mossing, Christina Lu, Paul C. Bogdan, Emmanuel Ameisen, James Chen, Dzmitry Kishylau, Adam Pearce, Julius Tarng, Alex Wu, Jeff Wu, Yang Zhang, Daniel M. Ziegler, Evan Hubinger, Joshua Batson, Jack Lindsey, Samuel Zimmerman, and Samuel Marks [May 2026]. ***Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations.*** URL: <https://transformer-circuits.pub/2026/nla/> [visited on 06/05/2026].
-  Johnson, William B. and Joram Lindenstrauss [1984]. **“Extensions of Lipschitz Mappings into a Hilbert Space”**. In.
-  Karvonen, Adam, James Chua, Clément Dumas, Kit Fraser-Taliente, Subhash Kantamneni, Julian Minder, Euan Ong, Arnab Sen Sharma, Daniel Wen, Owain Evans, and Samuel Marks [Jan. 2026]. ***Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers.*** URL: <http://arxiv.org/abs/2512.15674> [visited on 03/30/2026].

-  Karvonen, Adam, Can Rager, Johnny Lin, Curt Tigges, Joseph Bloom, David Chanin, Yeu-Tong Lau, Eoin Farrell, Callum McDougall, Kola Ayonrinde, Demian Till, Matthew Wearden, Arthur Conmy, Samuel Marks, and Neel Nanda [June 2025]. ***SAEBench: A Comprehensive Benchmark for Sparse Autoencoders in Language Model Interpretability.*** URL: <http://arxiv.org/abs/2503.09532> [visited on 03/30/2026].
-  Li, Kenneth, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg [June 2024]. ***Inference-Time Intervention: Eliciting Truthful Answers from a Language Model.*** URL: <http://arxiv.org/abs/2306.03341> [visited on 03/31/2026].

-  Lindsey, Jack, Wes Gurnee, Emmanuel Ameisen, Brian Chen, Adam Pearce, Nicholas L. Turner, Craig Citro, David Abrahams, Shan Carter, Basil Hosmer, Jonathan Marcus, Michael Sklar, Adly Templeton, Trenton Bricken, Callum McDougall, Hoagy Cunningham, Thomas Henighan, Adam Jermy, Andy Jones, Andrew Persic, Zhenyi Qi, T. Ben Thompson, Sam Zimmerman, Kelley Rivoire, Thomas Conerly, Chris Olah, and Joshua Batson [Mar. 2025]. ***On the Biology of a Large Language Model***. URL: <https://transformer-circuits.pub/2025/attribution-graphs/biology.html>.
-  Lindsey, Jack, Adly Templeton, Jonathan Marcus, Thomas Conerly, Joshua Batson, and Christopher Olah [Oct. 2024]. ***Sparse Crosscoders for Cross-Layer Features and Model Diffing***. URL: <https://transformer-circuits.pub/2024/crosscoders/index.html>.
-  McDougall, Callum [Jan. 2023]. “**Induction Heads - Illustrated — LessWrong**”. In: URL: <https://www.lesswrong.com/posts/TvrfY4c9eaGLeyDkE/induction-heads-illustrated> [visited on 04/02/2026].

-  Mikolov, Tomas, Wen-tau Yih, and Geoffrey Zweig [June 2013]. “**Linguistic Regularities in Continuous Space Word Representations**”. In: *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. Atlanta, Georgia: Association for Computational Linguistics. URL: <https://aclanthology.org/N13-1090/> [visited on 03/30/2026].
-  Nanda, Neel [Mar. 2022]. “**A Longlist of Theories of Impact for Interpretability**”. In: URL: <https://www.lesswrong.com/posts/uK6sQCNMw8WKzJeCQ/a-longlist-of-theories-of-impact-for-interpretability> [visited on 03/31/2026].
-  Nanda, Neel, Lawrence Chan, Tom Lieberum, Jess Smith, and Jacob Steinhardt [Jan. 2023]. ***Progress Measures for Grokking via Mechanistic Interpretability***. URL: <https://arxiv.org/abs/2301.05217>.

-  Nanda, Neel, Andrew Lee, and Martin Wattenberg [2023]. **“Emergent Linear Representations in World Models of Self-Supervised Sequence Models”**. In: *Proceedings of the 6th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*. Singapore: Association for Computational Linguistics. URL: <https://aclanthology.org/2023.blackboxnlp-1.2> [visited on 03/30/2026].
-  nostalgebraist [Aug. 2020]. ***Interpreting GPT: The Logit Lens***. URL: <https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens>.
-  Olah, Chris, Nick Cammarata, Ludwig Schubert, Gabriel Goh, Michael Petrov, and Shan Carter [Mar. 2020]. **“Zoom In: An Introduction to Circuits”**. In: *Distill* 5.3. URL: <https://distill.pub/2020/circuits/zoom-in> [visited on 03/30/2026].
-  Panickssery, Nina, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner [July 2024]. ***Steering Llama 2 via Contrastive Activation Addition***. URL: <http://arxiv.org/abs/2312.06681> [visited on 08/12/2025].

-  Park, Kiho, Yo Joong Choe, and Victor Veitch [July 2024]. **“The Linear Representation Hypothesis and the Geometry of Large Language Models”**. In.
-  Rajamanoharan, Senthooan, Arthur Conmy, Lewis Smith, Tom Lieberum, Vikrant Varma, János Kramár, Rohin Shah, and Neel Nanda [Apr. 2024]. **“Improving Dictionary Learning with Gated Sparse Autoencoders”**. In.
-  Sharkey, Lee, Bilal Chughtai, Joshua Batson, Jack Lindsey, Jeff Wu, Lucius Bushnaq, Nicholas Goldowsky-Dill, Stefan Heimersheim, Alejandro Ortega, Joseph Bloom, Stella Biderman, Adria Garriga-Alonso, Arthur Conmy, Neel Nanda, Jessica Rumbelow, Martin Wattenberg, Nandi Schoots, Joseph Miller, Eric J. Michaud, Stephen Casper, Max Tegmark, William Saunders, David Bau, Eric Todd, Atticus Geiger, Mor Geva, Jesse Hoogland, Daniel Murfet, and Tom McGrath [Jan. 2025]. ***Open Problems in Mechanistic Interpretability***. URL: <http://arxiv.org/abs/2501.16496> [visited on 03/30/2026].

-  Templeton, Adly, Tom Conerly, Jonathan Marcus, Jack Clark, Yan Shlegeris, Trenton Bricken, Aidan O’Gara, Emmanuel Ameisen, Adam Jermy, Baobao Zhang, Chris Olah, and Sam McCandlish [May 2024]. ***Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet.*** URL: <https://transformer-circuits.pub/2024/scaling-monosemanticity/> [visited on 03/26/2026].
-  Wang, Kevin, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt [Nov. 2022]. ***Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small.*** URL: <https://arxiv.org/abs/2211.00593>.
-  Wentworth, John [Aug. 2020]. **“Alignment By Default — LessWrong”**. In: URL: <https://www.lesswrong.com/posts/Nwgdq6kHke5LY692J/alignment-by-default> [visited on 03/31/2026].